



STYROZYD ECO

DECLARATION OF PERFORMANCE

No. F-01/21.07.2026

1. Unique identification code of the product type

Ceramic Tile Adhesive – C2TES1

2. Type, batch or serial number or any other element allowing identification of the construction product in accordance with Article 11(4)

Ceramic Tile Adhesive – C2TES1

Batch No.: See product label.

3. Intended use(s) of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer

Ceramic Tile Adhesive – C2TES1 is intended for the installation of ceramic tiles on interior and exterior walls, floors and ceilings.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer in accordance with Article 11(5)

Trade Name: *High Performance FLEX Adhesive – Class C2TES1*

Manufacturer:

STYROZYD ECO Ltd. 10 Prodan Tarakchiev Str., Floor 2, Sofia 1540, Bulgaria E-mail: info@styrozyd.com

5. Contact address: Where applicable, the name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

STYROZYD ECO Ltd. 10 Prodan Tarakchiev Str., Floor 2, Sofia 1540, Bulgaria E-mail: info@styrozyd.com

6. System(s) of Assessment and Verification of Constancy of Performance (AVCP)

System 3

7. In case of the Declaration of Performance concerning a construction product covered by a harmonised standard

EN 12004:2007+A1:2012

Notified Body

**Research and Certification Centre for Construction Materials Ltd., 14 Asen Yordanov Blvd., Sofia,
Bulgaria**

Notified Body No. (NB): 3056, Type Testing Report No. PTD-040/16.07.2026

Declared Performance:

Essential Characteristic	Declared Performance	Test Method	Harmonized Technical Specification
Initial tensile adhesion strength	2,2 N/mm ²	EN 1348:2008 Clause 8.2	EN 12004:2007+A1:2012
Tensile adhesion strength after heat ageing	2,5 N/mm ²	EN 1348:2008 Clause 8.4	EN 12004:2007+A1:2012
Tensile adhesion strength after water immersion	1,9 N/mm ²	EN 1348:2008 Clause 8.3	EN 12004:2007+A1:2012
Tensile adhesion strength after freeze-thaw cycles	1,6 N/mm ²	EN 1348:2008 Clause 8.5	EN 12004:2007+A1:2012
Open time – tensile adhesion strength after at least 20 min	1,1 N/mm ²	EN 1346:2008	EN 12004:2007+A1:2012
Extended open time – tensile adhesion strength after at least 30 min	1,0 N/mm ²	EN 1346:2008	EN 12004:2007+A1:2012
Slip	0,2 mm	EN 1308:2009	EN 12004:2007+A1:2012
Transverse deformation	2,9 mm	EN 12002:2009	EN 12004:2007+A1:2012



The performance of the product identified above is in conformity with the declared performance shown in this Declaration of Performance.

This Declaration of Performance is issued under the sole responsibility of the manufacturer:

STYROZYD ECO Ltd.

Managing Director:

/ Nevena Tahtakova-Ivandzhikova/

STYROZYD ECO Ltd.

Sofia, Bulgaria

21.07.2026 r.

	
26	
STYROZYD ECO Ltd. 10 Prodan Tarakchiev Str., Floor 2, 1540 Sofia, Bulgaria	
F-01/21.07.2026	
EN 12004:2007+A1:2012	
Ceramic Tile Adhesive – C2TES1	
For the installation of ceramic tiles on interior and exterior walls, floors and ceilings.	
AVCP System: System 3	
Notified Body: NB 3056	
Essential Characteristic	Declared Performance
Initial tensile adhesion strength	2,2 N/mm ²
Tensile adhesion strength after heat ageing	2,5 N/mm ²
Tensile adhesion strength after water immersion	1,9 N/mm ²
Tensile adhesion strength after freeze-thaw cycles	1,6 N/mm ²
Open time – tensile adhesion strength after at least 20 min	1,1 N/mm ²
Extended open time – tensile adhesion strength after at least 30 min	1,0 N/mm ²
Slip	0,2 mm
Transverse deformation	2,9 mm
www.styrozyd.com	